

		A4F		M		/		W		-											
液压油																					
HFD 矿物油(无标识)																					
HFA、HFB、HFC 液压油(仅适用于规格 71...500)		E-																			
轴向柱塞元件																					
定量, 斜盘结构		A4F																			
工作方式																					
马达		M																			
规格																					
a 排量 V_g (cm ³)		22	28	40	56	71	125	250	500												
		●	●	●	●	●	●	●	○												
系列																					
		规格 22...56, 125...500										3									
		规格 71										1									
标号																					
		规格 22...56										2									
		规格 71...500										0									
旋转方向																					
在轴端看		双向可逆										W									
密封																					
丁腈橡胶, 轴封为氟橡胶		规格 22...56										N									
		规格 71...500										P									
氟橡胶		规格 71...500										V									
轴伸		22	28	40	56	71	125	250	500												
花键轴 SAE		○	○	-	-	-	-	-	-	S											
花键轴 SAE		●	●	-	-	-	-	-	-	T											
花键轴 DIN 5480		-	-	●	●	●	●	●	○	Z											
带键直轴 DIN 6885		-	-	-	-	●	●	●	○	P											
安装法兰		22	28	40	56	71	125	250	500												
SAE 2-孔		●	●	●	●	-	-	-	-	C											
ISO 4-孔		-	-	-	-	●	●	●	-	B											
ISO 8-孔		-	-	-	-	-	-	-	○	H											
工作管路油口		22...40										56		71...500							
油口 A, B: SAE, 位于后部(公制固定螺纹)		-										●		●		01					
油口 A, B: SAE, 位于侧面(公制固定螺纹)		●										-		●		02					

