

订货型号											
工作液体/种类	40	71	125	180	250	355	500	750	1000		
矿物油 (无代号)	●	●	●	●	●	●	●	●	●		
HF液体 (防护、液压油等特种液压油除外)	●	●	●	●	●	●	●	—	—	E	
高速型系列	—	—	—	—	●	●	●	—	—	H	
轴向柱塞元件											
变量泵, 斜盘结构, 为工业用										A4VS	
增压泵 (吸入增压)	40	71	125	180	250	355	500	750	1000		
无增压泵 (无代号)	●	●	●	●	●	●	●	●	●		
仅25型带增压泵 (吸入增压)	—	—	—	—	—	—	—	●	—	L	
运行模式											
泵, 开式回路										O	
规格											
△ 排量 $V_{g \max} (cm^3)$	40	71	125	180	250	355	500	750	1000		
控制机构											
压力控制	DR	●	●	●	●	●	●	●	●	DR..	见 RC 92 060
流量控制	FR	●	●	●	●	●	—	—	—	FR..	
按双曲线变化的功率控制	LR	●	●	●	●	●	●	●	○	LR..	见 RC 920 64
手动控制	MA	●	●	●	●	●	●	—	—	MA..	见 RC 92 072
电机控制	EM	●	●	●	●	●	●	—	—	EM..	
机械液压控制	HW	●	●	●	●	●	●	●	○	HW..	见 RC 92 068 (准备中)
和容积有关的液压控制	HM	●	●	●	●	●	●	●	○	HM..	
带比例/伺服阀的液压控制	HS	●	●	●	●	●	●	●	○	HS..	见 RC 92 076
电控	EO	●	●	●	●	●	●	●	○	EO..	
和压力有关的液压控制	HD	●	●	●	●	●	●	●	○	HD..	见 RC 92 080
速度控制, 二次调节	DS	●	●	●	●	●	●	●	○	DS..	见 RC 92 055
系列											
	●	●	—	—	—	—	—	—	—	10	
	—	—	●	●	—	●	—	—	—	22	
	—	—	○	○	●	○	●	●	●	30	
转动方向											
从轴端看										顺时针 R	
										逆时针 L	
密封											
带FPM轴封的NBR (丁腈橡胶, 符合DIN ISO 1629)										P	
FPM (氟橡胶, 符合DIN ISO 1629)										V	
轴伸											
带键直轴 DIN 6885										P	
花键轴, DIN 5480										Z	
按装法兰											
ISO 4孔	40	71	125	180	250	355	500	750	1000		
ISO 8孔	—	—	—	—	—	—	●	●	●	H	

● = 有货
○ = 无货
— = 在准备中

■ = 首选方案 (较短的交货时间)
(首选型号请见第39页)